

## tesa® 51495 PV2 Reinforced Aluminium Foil Tape

tesa® 51495 PV2 consists of aluminium foil reinforced with polyethylene scrim which is coated with a rubber/resin adhesive.

### Features:

- Release liner for ease of unwind
- Thermal insulation properties
- Vapour barrier
- Heat and radiation reflective properties
- Excellent adhesion to own backing
- High bond strength
- High initial adhesion

### Main Application

- Joining roofing and wall insulation
- Pipewrapping and insulation
- Joining and sealing air conditioning duct insulation

### Technical Data

▪ Backing material	Aluminium foil reinforced with PE scrim	▪ Total thickness	205 µm
▪ Release liner	Silicone coated paper	▪ Service temperature	-20°C to 80°C
▪ Adhesive	Rubber/resin	▪ Tensile strength	115 N/25mm
▪ Colour	Silver	▪ Elongation at break	25%
		▪ Adhesion to steel	30 N/25mm

### AS/NZS 1530.3:1999

▪ Ignitability Index (0-20)	0
▪ Spread of Flame Index	0
▪ Heat Evolved Index	0
▪ Smoke Developed Index	0-1

For latest information on this product please visit [www.tesatape.com.au](http://www.tesatape.com.au)

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.