

Copper Plumbing Fittings

COPPER AND
COPPER ALLOY
PLUMBING
FITTINGS



USAGE

Pressure and non-pressure applications including:

- Plumbing
- Gas Fittings
- Drainage

BENEFITS

- Backed by MM Kembla's reputation for quality, service and customer care for nearly 100 years.
- Manufactured to Australian Standard AS3688.
- Safe. Does not burn or support combustion. Max service temp of 200°C.
- Kembla Plumbing Fittings are stocked for prompt nationwide delivery.

FEATURES

- Copper capillary pressure fittings, which are marked AS3688, complement the safe working pressures of AS1432 Type B copper tubes of similar nominal diameter.
- In addition to capillary fittings, plumbers have a wide range of jointing options. Including dezincification resistant (DR) copper alloy compression and non-pressure fittings, and roll grooved fittings.
- All fittings comply with and are marked in accordance with relevant Australian Standards.
- Examples of common plumbing fittings are pictured overleaf.

INSTALLATION

- Jointing Methods – Copper tube can be easily joined using compression or capillary fittings with silver brazing alloys.
- MM Kembla Fittings meet various standards applicable to Copper and Copper Alloy fittings.
- There is a full range of Capillary, high-pressure and low-pressure plumbing fittings available in various sizes.

Copper Plumbing Fittings

MM Kembla's range of high quality copper plumbing fittings includes:

- Elbows - 45°, 85° & 90°
- High Pressure Elbows - 45° & 90°
- Tees – Equal and Reducing
- High Pressure Tees – Equal and Reducing
- Straight Connectors
- Concentric Reducers
- Elbows with Inspection Openings
- Copper Junctions
- Copper Junctions with Inspection Openings
- Caps and Linings
- Expansion Joints



For a detailed listing of copper plumbing fittings please visit the MM Kembla website.